

Varifocal Camera

MTC-2438

1/3" Hi-Res. Color Varifocal Dome Camera
Built-in Aspherical Lens

◆ Black or Ivory Finish Available

MTC-2338

1/3" Med-Res. Color Varifocal Dome Camera
Built-in Aspherical Lens



(Option:MTB-201 Bracket)

SPECIFICATIONS

	MTC-2438		MTC-2338	
TV System	PAL	NTSC	PAL	NTSC
Image Sensor	1/3" SONY Super HAD CCD			
Number of Total Pixels	795(H) X 596(V)	811(H) X 508(V)	537(H) X 597(V)	537(H) X 505(V)
Synchronizing System	Internal/Line Lock(AC Version Only)		Internal	
Resolution	480 TVL		420 TVL	
Minimum Illumination	0.18Lux@F1.2		0.15Lux@F1.2	
Signal to Noise Ratio	More Than 48dB(AGC Off)			
Automatic Gain Control	ON/OFF (Switchable)			
F.L. (Flickerless)	ON/OFF (Switchable)			
AES	ON/OFF (Switchable)			
Back Light Compensation	ON/OFF (Switchable)			
DC Level	The VR for adjusting the IRIS level of auto Iris lens.			
White Balance	2500°K~9200°K			
Video Output	1Vp-p Composite / 75 Ω			
Lens/Angle of view(H)	Standard:f3.8mm~9.5mm/F1.2 Aspherical Auto Iris Lens / 74.2°~30.0° Option:f2.5mm~6.0mm/F1.3 Aspherical Auto Iris Lens / 108.2°~47.6° Option:f9mm~22.0mm/F2.0 Auto Iris Lens / 29.2°~13.0°			
Power Supply	Standard:12Vdc ; Option:12Vdc/24Vac			
Power Consumption	2.5W		1.8W	
Operation Temperature	-10°C~+50°C			
Operation Humidity	RH85% or less			
Storage Temperature	-20°C ~ +60°C			
Dimensions	118(DIA) X 88(H)mm			
Weight	12Vdc: 300g; 12Vdc/24Vac: 370g			

DIMENSIONS

Video Out 12Vdc

