

## MZC-6018

1/4" 18x Indoor Speed Dome Camera  
Built-in Sony FCB-EX45 Series Zoom Camera

## MZC-IR6018DN

1/4" 18x Indoor D/N Speed Dome Camera  
Built-in Sony FCB-EX480 Series Zoom Camera  
Mechanical IR Cut Filter

## MZC-IR6026DN

1/4" 26x Indoor D/N Speed Dome Camera  
Built-in Sony FCB-EX980 Series Zoom Camera  
Mechanical IR Cut Filter

# Speed Dome Camera



## SPECIFICATIONS

	MZC-6018		MZC-IR6018DN		MZC-IR6026DN	
	PAL	NTSC	PAL	NTSC	PAL	NTSC
Image Sensor	1/4" Sony Super HAD CCD		1/4" Sony EXview HAD CCD		1/4" Sony EXview HAD CCD	
Number of Effective Pixels	440,000 Pixels	380,000 Pixels	440,000 Pixels	380,000 Pixels	440,000 Pixels	380,000 Pixels
Synchronizing System	Internal		Internal/External(V-Lock)			
Resolution			480 TVL			
Minimum Illumination	1.0 Lux@F1.4		0.7 Lux@F1.2		1.0 Lux@F1.6(50IRE)	
Video Output			1.0Vp-p			
Horizontal Resolution			More Than 480TVL			
Signal-to-Noise Ratio			≥ 50dB			
Electronic Shutter Speed Mode			1/1 ~ 1/10,000sec, 22 steps			
Iris			Auto/Manual			
Focus			Auto/Manual			
Lens	18x zoom f=4.1mm(wide)~73.8mm(tele),F1.4~F3.0				26x zoom f=3.5mm(wide)~91mm(tele),F1.6~F3.8	
Digital Zoom	12x (216x with Optical Zoom)				12x (312x with Optical Zoom)	
White Balance			Auto, ATW, Indoor, Outdoor, One-Push, Manual			
Black Light Compensation			ON/OFF			
Privacy Zone Masking			ON/OFF (6 Positions)		ON/OFF (24 Positions)	
Night Vision	N/A		IR cut filter removable and slow shutter on			
Panning Range			360° endless			
Panning Speed			0.5° ~ 250° /sec			
Tilt Range			0° ~ 90°			
Tilt Speed			0.5° ~ 130° /sec			
Communication			RS485			
Controls			Pan/Tilt, Lens, 80 preset positions			
Auto Pan			ON/OFF			
Auto Tracking Mode			ON/OFF, 4 cruising tracks			
Power Supply			24Vac			
Operation Temperature			-10°C ~ 40°C			
Dimensions			∅160(D) x 163.5(H)mm			
Weight			approx. 1.3Kg			

## DIMENSIONS

