

# Speed Dome Camera

## MZC-6218

1/4" 18x Indoor Speed Dome Camera  
Built-in Sony FCB-EX45 Series Zoom Camera

## MZC-IR6218DN

1/4" 18x Indoor D/N Speed Dome Camera  
Built-in Sony FCB-EX480 Series Zoom Camera  
Mechanical IR Cut Filter

## MZC-IR6226DN

1/4" 26x Indoor D/N Speed Dome Camera  
Built-in Sony FCB-EX980 Series Zoom Camera  
Mechanical IR Cut Filter



## SPECIFICATIONS

	MZC-6218		MZC-IR6218DN		MZC-IR6226DN	
	PAL	NTSC	PAL	NTSC	PAL	NTSC
Image Sensor	1/4" Sony Super HAD CCD		1/4" Sony EXview HAD CCD		1/4" Sony EXview HAD CCD	
Number of Effective Pixels	440,000 Pixels	380,000 Pixels	440,000 Pixels	380,000 Pixels	440,000 Pixels	380,000 Pixels
Synchronizing System	Internal		Internal/External(V-Lock)			
Resolution	480 TVL					
Minimum Illumination	1.0 Lux@F1.4		0.7 Lux@F1.2		1.0 Lux@F1.6(50IRE)	
Video Output	1.0Vp-p					
Horizontal Resolution	More Than 480TVL					
Signal-to-Noise Ratio	≥ 50dB					
Electronic Shutter Speed Mode	1/1 ~ 1/10,000sec, 22 steps					
Iris	Auto/Manual					
Focus	Auto/Manual					
Lens	18x zoom f=4.1mm(wide)~73.8mm(tele),F1.4~F3.0				26x zoom f=3.5mm(wide)~91mm(tele),F1.6~F3.8	
Digital Zoom	12x (216x with Optical Zoom)				12x (312x with Optical Zoom)	
White Balance	Auto, ATW, Indoor, Outdoor, One-Push, Manual					
Black Light Compensation	ON/OFF					
Privacy Zone Masking	ON/OFF (6 Positions)				ON/OFF (24 Positions)	
Night Vision	N/A		IR cut filter removable and slow shutter on			
Panning Range	360° endless					
Panning Speed	240°/sec					
Tilt Range	0° ~ 90°					
Tilt Speed	90°/sec					
Communication	RS485(RS422)					
Controls	64 preset positions					
Auto Pan	ON/OFF					
Auto Tracking Mode	Maximum 6 cruising tracks					
Power Supply	24Vac					
Operation Temperature	-10°C~40°C					
Dimensions	∅180(D) x 210(H)mm					
Weight	2Kg					

## DIMENSIONS

