

DHV-460/860/1660

Standalone DVR

4ch/8ch/16ch DVR
Wavelet Compression Format
USB Port for Transferring Data
Triplex & Networking Capability



SPECIFICATIONS

TV System	DHV-460		DHV-860		DHV-1660	
	PAL	NTSC	PAL	NTSC	PAL	NTSC
Video Input / Loop Through	BNC x 4		BNC x 8		BNC x 16	
Monitor Output			BNC x 1			
Audio Input / Output			RCA x2			
Compression Format			Wavelet			
Alarm Input	Dry contact x4		Dry contact x8		Dry contact x 16	
Control Output			x 1 (max. 1A, AC/DC)			
Communication Port			1 RS232			
Network Interface			1 RJ45(10/100 Base-T)			
Display Rate	100 pps	120 pps	200pps	240 pps	400 pps	480 pps
Recording Resolution	CIF		CIF, 1/2 D1		CIF, 1/2 D1	
Recording Rate (max)	100 pps	120 pps	100 pps	120 pps	100 pps	120 pps
Recording Quality			Low, Fair, Good, Better, Best			
Recording Mode			24hrs, Schedule, Alarm/Motion Trigger			
Display Resolution			PAL:720x576 ; NTSC:720x480 ; 520TVL			
Camera Title			Up to 8 characters			
Video Adjustment			Color, Contrast, Brightness on each camera			
Hard Disk			IDE type x1 (support 80, 120, 160, 200, 250GB)			
Playback Control			FF, Play, Rewind, Speed Up & Down			
Search Playback Index			Date/time, Alarm, Motion			
System Setup / OSD			Multi-language			
System Alarm			Video loss, Motion, Alarm, Hard Drive full			
Backup / Copy			USB 2.0			
Power Supply			90~260 Vac Switching Power(50/60Hz)			
Power Consumption	< 30 W		< 10 W		< 40 W	
Operation Temperature			-10°C ~ +45°C			
Dimension			425 W x 300D x 44H mm (16.74 W x 11.82D x 1.74 H inches)			
Net Weight(Without HDD)	< 4 kg (8.9 lbs)		< 4.5 kg (10 lbs)		< 4.6 kg (10.2 lbs)	

DIMENSIONS

DHV-1660

◆ Front View



◆ Rear View

