

# WTC-8342HQ

MPEG4 ASP Compression  
 Resolution up to Full D1  
 SONY HQ1/ 550TVL  
 Minimum Illumination: 0.15Lux@F1.0

# HQ1 MPEG4 IP Camera



Standard packing does not include lens.

## SPECIFICATIONS

		WTC-8342HQ	
		PAL	NTSC
Image System	TV System	PAL	NTSC
	Image Sensor	1/3" SONY Super HAD CCD	
	DSP	SONY HQ1	
	Effective Pixels(H x V)	795(H) x 697(V)	811(H) x 508(V)
	Resolution	550TVL	
	Synchronizing System	Internal	
	Minimum Illumination	0.15Lux @ F1.0	
	Electronic Shutter	AES On: 1/50 (60) sec. ~ 1/100,000 sec; AES Off: 1/50 (60) sec.	
	Back Light Compensation	ON/ OFF (Switchable)	
	Auto Gain Control	ON/ OFF (Switchable)	
	Flicker Less	ON/ OFF (Switchable)	
	Auto IRIS Control	Video / DC (Switchable)	
	Auto White Balance	AWB (ATW)	
	Signal to Noise Ratio	More than 50dB (AGC off)	
Video Output	1Vp-p Composite/75 Ω		
Lens Mount	C/CS (With Adaptor)		
Compression	Image Compression	MPEG4 ASP	
	Image Frame Rate	25 fps @ 720x576	30 fps @ 720x480
	Max Resolution	Full D1 / CIF / QCIF	
Network	Ethernet	10/100 base-T for LAN/WAN	
	Supported Protocol	TCP/IP, HTTP, ARP, PPPoE, DDNS, DHCP, RTP/RTSP,IGMP	
	QoS	Layer 2, 3	
I/O Connector	Network	2xRJ-45 (WAN/LAN)	
	Analog Video Output	1xComposite ( BNC )	
	Serial Port	1xRJ-45 port ( RS485 )	
	DI/O	1xDI ;1xDO	
Software OS Support	Win 2000, Win XP / 16Ch AP		
Watchdog Timer	5 sec.		
Security	User authorization for accessing camera		
Operation Temperature	-10°C to +50°C		
Operation Humidity	RH85% or less		
Storage Temperature	- 20°C to +60°C		
Power Supply	12Vdc		
Power Consumption	9.0W		
Dimensions	63(W)x52(H)x120(L) mm		
Weight	600g		

## DIMENSIONS

